

RAD SINGLE SPEED 10GX



Part Number: **12818**



LIGHTER FASTER STRONGER

More than 30 years of experience in gearbox engineering and design has brought about our latest generation in planetary gearboxes – RAD Single Speed. Designed for extreme duty use in a variety of industries worldwide.

SPECIFICATIONS

Torque Ranges: 200 ft. lbs. – 1000 ft. lbs.

Speed: 20 RPM

Weight: 8.0 lbs.


Square Drive: 0.75"

Noise Level: 80 dB

Repeatability: +/-2%

Accuracy: +/-4%

DIMENSIONS



DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
8.15"	2.5"	2.75"	8.07"



Non
Impacting



Safe &
Reliable



Class 1 Division
2 Group A, B,
C, D T4



Accredited
ISO/IEC 17025

Included Tool Holder

With FRL unit, 12' hose and fittings



SUITABLE REACTION ARMS

Standard

PN: 19260



Deep Socket

PN: 13367



Double Ended Arm

PN: 13368



Blank

PN: 13364



Double Ended Blank

PN: 13365



Retaining Ring

PN: 12733



RAD SINGLE SPEED 14GX-M

Part Number: **13549**



LIGHTER FASTER STRONGER

More than 30 years of experience in gearbox engineering and design has brought about our latest generation in planetary gearboxes – RAD Single Speed. Designed for extreme duty use in a variety of industries worldwide.

SPECIFICATIONS

Torque Ranges: 275 Nm – 1400 Nm

Speed: 20 RPM

Weight: 3.8 Kg


Square Drive: 0.75"

Noise Level: 80 dB

Repeatability: +/-2%

Accuracy: +/-4%

DIMENSIONS



DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
228 mm	63 mm	70 mm	228 mm



Non
Impacting



Safe &
Reliable



Class 1 Division
2 Group A, B,
C, D T4



Accredited
ISO/IEC 17025

Included Tool Holder

With FRL unit, 12' hose and fittings



SUITABLE REACTION ARMS

Standard

PN: 19260



Deep Socket

PN: 13367



Double Ended Arm

PN: 13368



Blank

PN: 13364



Double Ended Blank

PN: 13365



Retaining Ring

PN: 12733



NEW WORLD TECHNOLOGIES INC

#100 - 30722 MARSHALL RD | ABBOTSFORD, BC V2T 0H9 | CANADA
604.852.0405 | INFO@RADTORQUE.COM | RADTORQUE.COM