

RAD SINGLE SPEED 80DX



Part Number: **18558**



LIGHTER FASTER STRONGER

More than 30 years of experience in gearbox engineering and design has brought about our latest generation in planetary gearboxes – RAD Single Speed. Designed for extreme duty use in a variety of industries worldwide.

SPECIFICATIONS

Torque Ranges: 2500 ft. lbs. – 8000 ft. lbs.

Speed: 4 RPM

Weight: 30.5 lbs.


Square Drive: 1.5"

Noise Level: 85 dB

Repeatability: +/-2%

Accuracy: +/-4%

DIMENSIONS



DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
12.15"	4.25"	4.25"	10.65"



Non
Impacting



Safe &
Reliable



Class 1 Division
2 Group A, B,
C, D T4



Accredited
ISO/IEC 17025

Included Tool Holder

With FRL unit, 12' hose and fittings



SUITABLE REACTION ARMS

Standard

PN: 23144



Deep Socket

PN: 13508



Double Ended Arm

PN: 13509



Blank

PN: 13505



Double Ended Blank

PN: 13506



Retaining Ring

PN: 11930



RAD SINGLE SPEED 110DX-M

Part Number: **23229**



LIGHTER FASTER STRONGER

More than 30 years of experience in gearbox engineering and design has brought about our latest generation in planetary gearboxes – RAD Single Speed. Designed for extreme duty use in a variety of industries worldwide.

SPECIFICATIONS

Torque Ranges: 3400 Nm - 11000 Nm

Speed: 4 RPM

Weight: 13.7 Kg


Square Drive: 1.5"

Noise Level: 85 dB

Repeatability: +/-2%

Accuracy: +/-4%

DIMENSIONS



DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
308 mm	108 mm	108 mm	270 mm



Non
Impacting



Safe &
Reliable



Class 1 Division
2 Group A, B,
C, D T4



Accredited
ISO/IEC 17025

Included Tool Holder

With FRL unit, 12' hose and fittings



SUITABLE REACTION ARMS

Standard

PN: 23144



Deep Socket

PN: 13508



Double Ended Arm

PN: 13509



Blank

PN: 13505



Double Ended Blank

PN: 13506



Retaining Ring

PN: 11930

