

B-RAD X 5000

Imperial Part No. 30656

SPECIFICATIONS

Torque Range Ft. lbs.: 500 - 5,000 Ft. lbs.
Torque Range Nm: 700 - 7,000 Nm
Speed: 3 RPM
Weight: 10.5 Kg (including battery, excluding reaction arm and impact socket)
Square Drive: 1 1/2"
Noise Level: 87 dB
Accuracy: +/- 4%
Repeatability: +/- 2%
Motor Type: Brushless
Features: Torque and Angle function
Metric Equivalent: B-RAD X 7000-M Part No. 30657


INCLUDED

- B-RAD X 5000 Tool
- Cast Arm (PN 25665)
- Retaining Ring (PN: 10032)
- X 2 18V 8.0 Ah/144 Wh Li-ion battery
- Charging Station
- Instruction Manual and Safety Guide
- Calibration Certificate
- Weatherproof storage case
- Tool Handle/Hanger (PN:26674)

DIMENSIONS



REACTION ARMS

CAST ARM  PN: 25665 (included in kit)	ANGLED DEEP SOCKET  PN: 26118
90 DEGREE STANDARD  PN: 29422	90 DEGREE DEEP  PN: 29425
DOUBLE ENDED  PN: 26119	STANDARD SLIDING 90 - 250mm  PN: CRP20248-1

SAFETY

REAR HANDLE  PN: 30391	SOFT SLING  PN: 30393
TOP HANDLE  PN: 30392	TOOL HANDLE ONE EYE  PN: 26674

Adelaide (HQ)
7 MAB Eastern Promenade
Tonsley SA 5042
(08) 8299 0355
sa@radicaltorque.com.au

Perth
1/184 Railway Parade
Bassendean WA 6054
(08) 6118 2710
wa@radicaltorque.com.au

Brisbane
25/121 Kerry Road
Archerfield QLD 4108
(07) 3063 9597
qld@radicaltorque.com.au

Mackay
10 Peace Street
Paget, QLD 4740
+61 418 950 527
mackay@radicaltorque.com.au

Thailand
171/5 Soi On-nuch66, Suan Luang
Suan Luan, Bangkok 10250,
Thailand
+66 (0)2 130 5208
thailand@radicaltorque.com