

B-RAD X 8000

Part No. 30658

SPECIFICATIONS

Torque Range Ft. lbs.: 740 - 8,000 Ft. lbs.
Torque Range Nm: 1,000 - 10,000 Nm
Speed: 2 RPM
Weight: 13.8 Kg (including battery, excluding reaction arm and impact socket)
Square Drive: 1 1/2"
Noise Level: 87 dB
Accuracy: +/- 4%
Repeatability: +/- 2%
Motor Type: Brushless
Features: Torque and Angle function
Metric Equivalent: B-RAD X 10K Part No. 30661



INCLUDED

- B-RAD X 8000 Tool
- Cast Reaction Arm (PN: 23144)
- Retaining Ring (PN: 11930)
- X 2 18V 8.0 Ah/144 Wh Li-ion battery
- Charging Station
- Instruction Manual and Safety Guide
- Calibration Certificate
- Weatherproof storage case
- Tool Handle/Hanger (PN: 22931)

DIMENSIONS



REACTION ARMS

CAST ARM  PN: 23144 (included in kit)	ANGLED DEEP SOCKET  PN: 13508
90 DEGREE  PN: 12885	90 DEGREE DEEP  PN: 13508
DOUBLE ENDED  PN: 13509	RETAINING RING  PN: 11930 (included in kit)

SAFETY

REAR HANDLE  PN: 30391	SOFT SLING  PN: 30393
TOP HANDLE  PN: 30392	TOOL HANDLE ONE EYE  PN: 22931 (included in kit)

Adelaide (HQ)
 7 MAB Eastern Promenade
 Tonsley SA 5042
 (08) 8299 0355
 sa@radicaltorque.com.au

Perth
 1/184 Railway Parade
 Bassendean WA 6054
 (08) 6118 2710
 wa@radicaltorque.com.au

Brisbane
 25/121 Kerry Road
 Archerfield QLD 4108
 (07) 3063 9597
 qld@radicaltorque.com.au

Mackay
 10 Peace Street
 Paget, QLD 4740
 +61 418 950 527
 mackay@radicaltorque.com.au

Thailand
 171/5 Soi On-nuch66, Suan Luang
 Suan Luan, Bangkok 10250,
 Thailand
 +66 (0)2 130 5208
 thailand@radicaltorque.com