

DB-RAD 500-2

Imperial Part No. 21779-A

SPECIFICATIONS

Torque Range Ft. lbs: 50 - 500 Ft. lbs
Torque Range Nm: 70 - 700 Nm
Speed: 59 RPM
Weight: 5 Kg
Square Drive: 3/4"
Noise Level: 80 dBA
Accuracy: +/- 5%
Repeatability: +/-2%
Motor Type: Brushless
Features: Torque and Angle function
Metric Equivalent: DB-RAD 700-2-M Part No. 22876





INCLUDED

- Digital B-RAD 500-2 tool
- Reaction Arm (PN: 19260)
- Retaining Ring (PN: 12733)
- X 2 18V Li-ion batteries 5.2 Ah/93 Wh
- Charging Station
- Instruction Manual and Safety Guide
- Calibration Certificate
- Weatherproof storage case

DIMENSIONS



REACTION ARMS

ANGLED  PN: 17235	ANGLED DEEP SOCKET  PN: 17236	90 DEGREE  PN: 13366	90 DEGREE DEEP SOCKET  PN: 13367
DOUBLE ENDED  PN: 13368	SLIDING ARM  PN: CRP12818-1	CAST ARM  PN: 19260 (included in kit)	RETAINING RING  PN: 12733 (included in kit)

Adelaide (HQ)
 7 MAB Eastern Promenade
 Tonsley SA 5042
 (08) 8299 0355
sa@radicaltorque.com.au

Perth
 1/184 Railway Parade
 Bassendean WA 6054
 (08) 6118 2710
wa@radicaltorque.com.au

Brisbane
 25/121 Kerry Road
 Archerfield QLD 4108
 (07) 3063 9597
qld@radicaltorque.com.au

Mackay
 10 Peace Street
 Paget, QLD 4740
 +61 418 950 527
mackay@radicaltorque.com.au

Thailand
 171/5 Soi On-nuch66, Suan Luang
 Suan Luan, Bangkok 10250,
 Thailand
 +66 (0)2 130 5208
thailand@radicaltorque.com