

E-RAD BLU 11K-S

NEW!



Part Number: **29314**




LIGHTER **FASTER** STRONGER

The E-RAD BLU-S is the newest addition to the E-RAD BLU product line from RAD. Equipped with a transducer, the E-RAD BLU-S allows for the highest accuracy on the market and features operator identification, which ensures traceability of each torque sequence performed. With a pass/fail indicator on both sides, and password protection, you'll be sure you're getting controlled and accurate torquing.

SPECIFICATIONS

Torque Ranges:
3000 ft. lbs. - 11,000 ft. lbs.
Speed: 1.5 RPM
Weight: 44 lbs.
Square Drive: 1.5"
Noise Level: 75 dB
Repeatability: +/-2
Accuracy: +/-1%

DIMENSIONS



| DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D |
|----------------|----------------|----------------|----------------|
| 19.81" | 5.21" | 3.48" | 11.29" |



Non
Impacting



Safe &
Reliable



Class 1 Division
2 Group A, B,
C, D T4



Accredited
ISO/IEC 17025



Accredited
ISO/IEC 17025

ACCESSORIES

E-RAD BLU Touch Control Case



SUITABLE REACTION ARMS

Standard
PN:



Deep Socket
PN:



Double Ended Arm
PN:



Blank
PN:



Double Ended Blank
PN:



Retaining Ring
PN:



NEW WORLD TECHNOLOGIES INC

#100 - 30722 MARSHALL RD | ABBOTSFORD, BC V2T 0H9 | CANADA
604.852.0405 | INFO@RADTORQUE.COM | RADTORQUE.COM

E-RAD BLU 15K-M

NEW!



Part Number: **29315**




LIGHTER **FASTER** STRONGER

The E-RAD BLU-S is the newest addition to the E-RAD BLU product line from RAD. Equipped with a transducer, the E-RAD BLU-S allows for the highest accuracy on the market and features operator identification, which ensures traceability of each torque sequence performed. With a pass/fail indicator on both sides, and password protection, you'll be sure you're getting controlled and accurate torquing.

SPECIFICATIONS

Torque Ranges:
4050 Nm - 15,000 Nm
Speed: 1.5 RPM
Weight: 20 KG
Square Drive: 1.5"
Noise Level: 75 dB
Repeatability: +/-2
Accuracy: +/-1%

DIMENSIONS



| DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D |
|----------------|----------------|----------------|----------------|
| 503 mm | 132 mm | 88 mm | 287 mm |



Non
Impacting



Safe &
Reliable



Class 1 Division
2 Group A, B,
C, D T4



Accredited
ISO/IEC 17025

ACCESSORIES

E-RAD BLU Touch Control Case



SUITABLE REACTION ARMS

Standard
PN:



Deep Socket
PN:



Double Ended Arm
PN:



Blank
PN:



Double Ended Blank
PN:



Retaining Ring
PN:



NEW WORLD TECHNOLOGIES INC

#100 - 30722 MARSHALL RD | ABBOTSFORD, BC V2T 0H9 | CANADA
604.852.0405 | INFO@RADTORQUE.COM | RADTORQUE.COM