

# E-RAD BLU 3000-S

**NEW!**



Part Number: **31190**




## LIGHTER **FASTER** STRONGER

The E-RAD BLU-S is the newest addition to the E-RAD BLU product line from RAD. Equipped with a transducer, the E-RAD BLU-S allows for the highest accuracy on the market and features operator identification, which ensures traceability of each torque sequence performed. With a pass/fail indicator on both sides, and password protection, you'll be sure you're getting controlled and accurate torquing.

### SPECIFICATIONS

Torque Ranges:  
500 ft. lbs. - 3000 ft. lbs.  
Speed: 5 RPM  
Weight: 24.5 lbs.  
Square Drive: 1"  
Noise Level: 75 dB  
Repeatability: +/-2  
Accuracy: +/-1%

### DIMENSIONS



DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
17.76"	3.73"	3.48"	11.29"



Non  
Impacting



Safe &  
Reliable



Class 1 Division  
2 Group A, B,  
C, D T4



Accredited  
ISO/IEC 17025



Accredited  
ISO/IEC 17025

### ACCESSORIES

E-RAD BLU Touch Control Case



### SUITABLE REACTION ARMS

**Standard**  
PN: 11531



**Deep Socket**  
PN: 11534



**Double Ended Arm**  
PN: 11533



**Blank**  
PN: 11530



**Double Ended Blank**  
PN: 11532



**Retaining Ring**  
PN: 11350



## NEW WORLD TECHNOLOGIES INC

#100 - 30722 MARSHALL RD | ABBOTSFORD, BC V2T 0H9 | CANADA  
604.852.0405 | INFO@RADTORQUE.COM | RADTORQUE.COM

# E-RAD BLU 4000-M

**NEW!**



Part Number: **22759**




LIGHTER **FASTER** STRONGER

The E-RAD BLU-S is the newest addition to the E-RAD BLU product line from RAD. Equipped with a transducer, the E-RAD BLU-S allows for the highest accuracy on the market and features operator identification, which ensures traceability of each torque sequence performed. With a pass/fail indicator on both sides, and password protection, you'll be sure you're getting controlled and accurate torquing.

## SPECIFICATIONS

Torque Ranges:  
675 Nm - 4000 Nm  
Speed: 5 RPM  
Weight: 11.1 KG  
Square Drive: 1"  
Noise Level: 75 dB  
Repeatability: +/-2  
Accuracy: +/-1%

## DIMENSIONS



DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
451 mm	95 mm	88 mm	287 mm



Non  
Impacting



Safe &  
Reliable



Class 1 Division  
2 Group A, B,  
C, D T4



Accredited  
ISO/IEC 17025

## ACCESSORIES

E-RAD BLU Touch Control Case



## SUITABLE REACTION ARMS

**Standard**  
PN: 11531



**Deep Socket**  
PN: 11534



**Double Ended Arm**  
PN: 11533



**Blank**  
PN: 11530



**Double Ended Blank**  
PN: 11532



**Retaining Ring**  
PN: 11350



**NEW WORLD TECHNOLOGIES INC**

#100 - 30722 MARSHALL RD | ABBOTSFORD, BC V2T 0H9 | CANADA  
604.852.0405 | INFO@RADTORQUE.COM | RADTORQUE.COM