

E-RAD BLU 700-S

NEW!



Part Number: **30079**




LIGHTER **FASTER** STRONGER

The E-RAD BLU-S is the newest addition to the E-RAD BLU product line from RAD. Equipped with a transducer, the E-RAD BLU-S allows for the highest accuracy on the market and features operator identification, which ensures traceability of each torque sequence performed. With a pass/fail indicator on both sides, and password protection, you'll be sure you're getting controlled and accurate torquing.

SPECIFICATIONS

Torque Ranges:
100 ft. lbs. – 700 ft. lbs.
Speed: 15 RPM
Weight: 13 lbs.
Square Drive: 0.75"
Noise Level: 75 dB
Repeatability: +/-2
Accuracy: +/-1%

DIMENSIONS



| DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D |
|----------------|----------------|----------------|----------------|
| 14.96" | 2.84" | 3.03" | 10.65" |



Non
Impacting



Safe &
Reliable



Class 1 Division
2 Group A, B,
C, D T4



Accredited
ISO/IEC 17025



ACCESSORIES

E-RAD BLU Touch Control Case



SUITABLE REACTION ARMS

Standard
PN: 19260



Deep Socket
PN: 13367



Double Ended Arm
PN: 13368



Blank
PN: 13364



Double Ended Blank
PN: 13365



Retaining Ring
PN: 12733



NEW WORLD TECHNOLOGIES INC

#100 - 30722 MARSHALL RD | ABBOTSFORD, BC V2T 0H9 | CANADA
604.852.0405 | INFO@RADTORQUE.COM | RADTORQUE.COM

E-RAD BLU 950-M

NEW!



Part Number: **26937**




LIGHTER **FASTER** STRONGER

The E-RAD BLU-S is the newest addition to the E-RAD BLU product line from RAD. Equipped with a transducer, the E-RAD BLU-S allows for the highest accuracy on the market and features operator identification, which ensures traceability of each torque sequence performed. With a pass/fail indicator on both sides, and password protection, you'll be sure you're getting controlled and accurate torquing.

SPECIFICATIONS

Torque Ranges:
135 Nm - 950 Nm
Speed: 15 RPM
Weight: 5.9 KG
Square Drive: 0.75"
Noise Level: 75 dB
Repeatability: +/-2
Accuracy: +/-1%

DIMENSIONS



| DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D |
|----------------|----------------|----------------|----------------|
| 380 mm | 72 mm | 77 mm | 270.5 mm |



Non
Impacting



Safe &
Reliable



Class 1 Division
2 Group A, B,
C, D T4



Accredited
ISO/IEC 17025

ACCESSORIES

E-RAD BLU Touch Control Case



SUITABLE REACTION ARMS

Standard
PN: 19260



Deep Socket
PN: 13367



Double Ended Arm
PN: 13368



Blank
PN: 13364



Double Ended Blank
PN: 13365



Retaining Ring
PN: 12733



NEW WORLD TECHNOLOGIES INC

#100 - 30722 MARSHALL RD | ABBOTSFORD, BC V2T 0H9 | CANADA
604.852.0405 | INFO@RADTORQUE.COM | RADTORQUE.COM